

Please copy one form per type and dimension and email the completed form to wearflex@insulcon.com.

From	
Company	Department
Name	Your reference
Email	Phone

Design data & operating conditions			
Type of kiln	Shuttle Periodic	Bell Continuous (tunnel kiln)	Other:
Inside dimensions of lining	L:	W:	H:
Dimensions of door (length x width)	L:	W:	
Type of door	Guillotine	2 half parts	1 part
Type of fired product			
Type of glaze (if applied)			
Fuel type	Gas	Oil	Electrical
Atmosphere	Oxidizing	Reducing	
Type of refractory lining	IFB Castable	Dense firebricks Ceramic fibre	
If ceramic fibre, which type of lining system	Blankets	Modules	Stackbond
Current situation	New lining	Existing lining	
If blanket lining, type of anchor system (pins + washer, cuplock etc.)			
Lining thickness			
Condition of hot surface	Soft	Brittle	
Condition of fixing (anchoring)			
Pattern of fixing			
Type of burners (gas velocity)			
Fluegas outlets: number, position (roof/wall)			
Dimensions fluegas outlet			
Temperature firing curve and/or maximum operating temperature			

In case of doubt, it is recommended to install a small test piece of Refrex® 1220/1420 fabric.

Insulcon B.V.
Zilverhoek 4
4651 SP Steenberg
The Netherlands
+31(0) 167 565750
info@insulcon.com

Keramab N.V.
Haverheidelaan 4
9140 Temse
Belgium
+32 (0) 3 7110278
sales@keramab.com

Insulcon GmbH
Weiserstr. 7
41468 Neuss
Germany
+49(0) 2131 408548-0
insulcongbh@insulcon.com

Insulcon Projects S.A.
Via Geretta 18
6900 Paradiso-Lugano
Switzerland
+41(0) 91911739-0
infoch@insulcon.com