

INSULATING FIRE BRICKS – ALL GRADES

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Relevant identified uses of the substance or mixture and uses advised against:

Identified uses: Refractory lining, back-up insulation

Uses advised against: None known

Identification of the company

INSULCON B.V.

Zilverhoek 4
4651 SP
The Netherlands
Tel. +31 (0)167 565750
Fax +31 (0)167 566263
www.insulcon.com
info@insulcon.com

INSULCON N.V.

Belgium
Tel. +32 (0)3 711.02.78
Fax +32 (0)3 711.08.56
www.insulcon.com

INSULCON GMBH

Germany
Tel. +49 (0)2131 408548-0
Fax +49 (0) 2131 408548-7
www.insulcon.com

2. HAZARDS IDENTIFICATION

OSHA/HCS status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture: CARCINOGENICITY - Category 1A
SPECIFIC TARGET ORGAN TOXICITY (STOT) REPEATED EXPOSURE – Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 0%

GHS label elements

Hazard



pictograms:

Signal word: Danger

Hazard statements: If dust is present:

Causes damage to lungs through prolonged or repeated exposure.

May cause cancer.

OSHA has determined the acceptable 8 hour exposure level for Respirable Crystalline Silica to be: 10 mg/m³ (%SiO₂ + 2)

Precautionary statements

Prevention: If dust is present:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection, face protection

Do not breathe dust.

Wash thoroughly after handling.

Do not eat, drink, or smoke while using this product.

INSULATING FIRE BRICKS – ALL GRADES

Response: If exposed, concerned, or feel unwell: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplementary Information: Use precautions if exposure exceeds the established OSHA limits. This material does not present a hazard unless dust is generated from cutting, grinding, or other operations.

Hazards not otherwise Classified: None known

3. COMPOSITION / INFORMATION ON INGREDIENTS

Substance or mixture: Mixture

Other means of identification: Insulating Fire Brick, IFB

CAS number/other identifiers

CAS number : Mixture

Product code : Insulating Fire Brick

Ingredient name	CAS number	%
Ceramic Matrix	Proprietary	60-98
Product contains :		
Crystalline Silica	14808-60-7	0.1-46
Crystalline Silica (cristobalite)	14464-46-1	0.1-22

Any concentration shown as a range it to protect confidentiality or is due to batch variation. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

4. FIRST AID MEASURES

Description of necessary first aid measures

Inhalation: Remove victim to fresh air.

Drink plenty of water and blow nose to evacuate remaining dust.

If coughing or irritation persist seek medical attention.

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids.

Check for and remove any contact lenses.

INSULATING FIRE BRICKS – ALL GRADES

Rinse for at least 15 minutes.
If irritation persists seek medical attention.

Skin contact: Gently wash with plenty of soap and water.
If irritation persists seek medical attention.

Ingestion Emergency procedures not normally required.
If prolonged irritation to gastrointestinal tract or mouth persist seek medical attention.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Inhalation: Respirable airborne particles may cause temporary irritation to the lungs and upper respiratory system.

Skin contact: Prolonged exposure may cause dryness or irritation to the skin.

Eye contact: Will cause mechanical irritation to the eyes. May cause moderate to severe eye irritation and dryness.

Ingestion: May cause irritation to gastrointestinal tract or mouth.

Over-exposure signs/symptoms

Inhalation: Adverse symptoms may include the following: Irritation

Eye contact: Adverse symptoms may include the following: Irritation, Dryness

Skin contact: Adverse symptoms may include the following: Irritation, Dryness

Ingestion: Adverse symptoms may include the following: Irritation, Stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician: Medical conditions which may be aggravated by exposure include dry skin, dermatitis, and pre-existing lung conditions such as bronchitis, emphysema, and asthma.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. Wear a suitable NIOSH-approved dust mask if airborne dust is present.

Wash contaminated clothing before re-use.

5. FIRE FIGHTING MEASURES

Specific hazards arising from the chemical:

None known other than those represented elsewhere in this SDS.

Hazardous thermal decomposition products

Decomposition products may include the following materials:

- Crystalline Silica

INSULATING FIRE BRICKS – ALL GRADES

During initial exposure to service temperatures, smoke may be emitted which can cause transitory irritation to the lungs and upper respiratory system.

Special protective actions for firefighters

Material will not burn.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

No action shall be taken involving any personal risk or without suitable training.

No special firefighting equipment is necessary.

Special protective equipment for fire-fighters

Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency Personnel

No action shall be taken involving any personal risk or without suitable training.

Evacuate surrounding areas.

Keep unnecessary and unprotected personnel from entering.

Provide adequate ventilation.

Wear appropriate respirator when ventilation is inadequate.

Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

This material does not pose a significant threat to the environment.

Avoid dispersion of material and runoff and contact with waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, or air)

Methods and materials for containment and cleaning up

Small spill

Stop source of spill.

Avoid creating airborne dust

Use dust suppressant as necessary

Place material into closed waste disposal container.

Any sweeper or vacuum should be equipped with High Efficiency Particulate (HEPA) filter.

Dispose of using a licensed waste disposal contractor.

Large spill

Stop source of spill.

Avoid creating airborne dust

Use dust suppressant as necessary

Place material into closed waste disposal container.

INSULATING FIRE BRICKS – ALL GRADES

Any sweeper or vacuum should be equipped with High Efficiency Particulate (HEPA) filter.
Dispose of using a licensed waste disposal contractor.
Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. HANDLING AND STORAGE

Protective measures for safe handling

Protective Measures:

Minimize dust generation

Use appropriate respiratory protection if dust is present above the established exposure limits.

If dusty conditions exist (such as during cutting, sanding, or milling) use engineering controls and/or respiratory protection (See Section 8).

Advice on general occupational hygiene

Eating and smoking should be prohibited in areas where this material is handled, stored and processed.

Workers should wash hands and face before eating and smoking.

Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Store in original container in a dry area, away from incompatible materials (see Section 10) and food and drink.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Occupational exposure limits:

US Occupational Safety and Health Administration Permissible Exposure Limit (OSHA PEL):

Irritant (Nuisance) Dust: 5 mg/m³

Crystalline Silica

Permissible Exposure Limit 50 µg/m³

Action Level 25 µg/m³

(See 29 CFR 1910.1053, effective June 23, 2018. Regulation contains additional requirements, including written exposure plan, medical exams, training, and recordkeeping.)

American Conference of Governmental and Industrial Hygienists Threshold Limit Value (ACGIH TLV®):

Irritant (Nuisance) Dust: 3mg/m³

Crystalline Silica 0.025 mg/m³

Note: TLV® and PEL values are for eight hour exposures, unless noted.

Appropriate Engineering controls:

If user operations generate dust, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Power equipment should be fitted with a properly designed dust collection device.

INSULATING FIRE BRICKS – ALL GRADES

Environmental Exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene Measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing.

Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory Protection:

Wear a NIOSH-approved dust mask to limit exposure to product dust.

Higher dust levels may require use of a half or full mask respirator with dust filters.

Use local exhaust if necessary to lower dust levels.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Eye/Face Protection:

Wear safety glasses with side shields or goggles complying with an approved standard to avoid exposure to dust.

Hand Protection:

Protective gloves should be worn when handling and to avoid abrasion or drying of skin.

Body Protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved.

Other Skin Protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	:	Solid blocks of various size
Color	:	Off-white to gray
Odor	:	None
Odor threshold	:	Not applicable
pH	:	Not applicable
Melting point	:	> 1260°C
Boiling point	:	N/A
Flash point	:	None
Burning time	:	Not applicable

INSULATING FIRE BRICKS – ALL GRADES

Specific gravity	:	1.5 – 1.7
Burning rate	:	Not applicable
Evaporation rate	:	0 (butyl acetate = 1)
Flammability (solid, gas)	:	Not applicable
Lower Explosive (flammable) limit	:	Not available
Upper Explosive (flammable) limit	:	Not available
Vapor Pressure	:	Not applicable
Vapor Density	:	Not applicable
Relative Density	:	Not available
Solubility	:	Insoluble
Solubility in Water	:	Insoluble
Partition coefficient: n-octanol/water	:	Not available
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
SADT	:	Not available
Viscosity	:	Not available

10. STABILITY AND REACTIVITY

Reactivity: This product is normally not reactive.

Chemical stability: The product is stable.

Possibility of Hazardous Reactions: Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to Avoid: Avoid strong acids and ammonium salts. Contact with strong oxidizing agents (such as fluorine, chlorine trifluoride) may present a fire hazard.

Incompatible Materials: Reactive or incompatible with the following materials:
Hydrofluoric acid, fluorine, chlorine trifluoride, oxygen difluoride

Hazardous Decomposition Products: Crystalline silica will dissolve in hydrofluoric acid and produce silicon tetrafluoride, a corrosive gas.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
None Known	--	--	--	--
	--	--	--	--

Irritation/Corrosion : Not available

Sensitization : Not available

Mutagenicity : Not available

Carcinogenicity : Not available

Reproductive toxicity : Not available

INSULATING FIRE BRICKS – ALL GRADES

Teratogenicity	:	Not available
Specific target organ toxicity (single exposure)	:	Not available
Specific target organ toxicity (repeated exposure)	:	This material contains Crystalline Silica, which is known to cause silicosis. Silicosis is a rapidly progressive, non-cancerous lung disease that is often fatal.
Aspiration hazard	:	Not available
Information on the likely routes of exposure	:	Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Inhalation : Respirable airborne particles may cause temporary irritation to the lungs and upper respiratory system.

Skin contact: Prolonged exposure may cause dryness or irritation to the skin.

Eye contact: Will cause mechanical irritation to the eyes. May cause moderate to severe eye irritation and dryness.

Ingestion: May cause irritation to gastrointestinal tract or mouth.
Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: Adverse symptoms may include the following: Irritation

Eye contact: Adverse symptoms may include the following: Irritation, Dryness

Skin contact: Adverse symptoms may include the following: Irritation, Dryness

Ingestion: Adverse symptoms may include the following: Irritation, Stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects: Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects: Not available.

Potential delayed effects : Not available.

Potential chronic health effects: Not available

General: No other known significant effects or critical hazards.

INSULATING FIRE BRICKS – ALL GRADES

Carcinogenicity: Crystalline silica – long term overexposure may cause permanent and irreversible lung damage, including silicosis, and increase the risk of lung cancer, kidney, and liver damage. Silicosis is a rapidly progressive, non-cancerous lung disease that is often fatal.

IARC (International Agency for Research on Cancer)

014808-60-7 Silica dust, crystalline, in the form of quartz or cristobalite - Group 1 (Sup 7, 68,100C, 2012)

National Toxicology Program (NTP) Report on Carcinogens

Silica, Crystalline (Respirable Size) - Known To Be Human Carcinogen

OSHA: Crystalline Silica classified as a Category 1A Carcinogen

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

12. ECOLOGICAL INFORMATION

Toxicity Not available.

Persistence and Degradability: Not available.

Bioaccumulative Potential: Not available.

Mobility in soil

Soil/water partition coefficient (K_{oc}): Not available

Other adverse effects: Most of the ingredients in this product are naturally occurring minerals, and, unless contaminated in service, are not hazardous to the environment.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way.

INSULATING FIRE BRICKS – ALL GRADES

Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with waterways, drains and sewers.

14. TRANSPORTATION INFORMATION

	<u>DOT Classification</u>	<u>TDG Classification</u>	<u>IMDG</u>	<u>IATA</u>
UN Number	Not Regulated	Not Regulated	Not Regulated	Not Regulated

Special precautions for user:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage

15. REGULATORY INFORMATION

U.S. Federal regulations

TSCA 8(a) CDR Exempt/Partial exemption: Not applicable

United States inventory (TSCA 8b): This material is listed.

Clean Air Act Section 112

(b) Hazardous Air

Pollutants (HAPs): Not listed

Clean Air Act Section 602

Class I Substances: Not listed

Clean Air Act Section 602

Class II Substances: Not listed

DEA List I Chemicals

(Precursor Chemicals): Not listed

DEA List II Chemicals

(Essential Chemicals): Not listed

SARA 302/304

Composition/information on ingredients: No products were found.

SARA 304 RQ: Not applicable.

INSULATING FIRE BRICKS – ALL GRADES

SARA 311/312

Classification :

Composition/information on ingredients:

Name	%	Immediate (acute) health hazard	Delayed (acute) health hazard	Fire hazard	Reactivity hazard	Sudden release of pressure
Ceramic Matrix	60-98	No	No	No	No	No
Crystalline Silica (Quartz)	0.1-46	Yes	Yes	No	No	No
Crystalline Silica (cristobalite)	0.1-22	Yes	Yes	No	No	No

Section 313 listed: No

Listed material/compound: Not Applicable

State regulations

New York: Crystalline Silica
New Jersey: Crystalline Silica
Pennsylvania: Crystalline Silica
Massachusetts: Crystalline Silica
Rhode Island: Crystalline Silica
California Prop. 65: Crystalline Silica

International Lists

DSL (Canada)

All ingredients are listed, or exempt from inclusion, on the Canadian Domestic Substances List (DSL).

Canada inventory (WHMIS see Sectopm 2)

Australia inventory (AICS): Not determined.

China inventory (IECSC): Not determined.

Japan inventory: Not determined.

Korea inventory: Not determined.

Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Taiwan inventory (CSNN): Not determined.

Chemical Weapons Convention List Schedule I Chemicals: Not listed

Chemical Weapons Convention List Schedule II Chemicals: Not listed

Chemical Weapons Convention List Schedule III Chemicals: Not listed

Insulcon B.V.- The Netherlands - Tel: +31 (0) 167 565750
Insulcon GmbH - Germany - Tel: +49 (0) 2131 408548-0
Insulcon N.V. - Belgium - Tel: +32 (0) 3 711 02 78
Insulcon Projects S.A. - Switzerland - Tel: +41 (0) 91911739-0

INSULCON

LEADER IN HIGH TEMPERATURE SOLUTIONS
www.insulcon.com

Form: B2-001
Effective: 06072022/ES
Supersedes: 17022022/ES/ka
All rights Reserved
LD: B181107

INSULATING FIRE BRICKS – ALL GRADES

DSCL (Europe): R

48/20: Harmful – Danger of serious damage to health by prolonged exposure through inhalation.

R36: Irritating to the eyes

R39: Danger of serious irreversible side effects.

R45: May cause cancer.

16. OTHER INFORMATION


Hazardous Material Information System (U.S.A.)

Health	2
Flammability	0
Physical Hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Insulcon believes the information contained in this Safety Data Sheet (SDS) to be accurate and reliable as of the date of issue, and is provided in good faith as a service to our customers and to comply with applicable laws. This document is intended as a guide for the safe handling, storage, and use of this material under normal conditions of use. No representation, warranty, or guarantee, either express or implied, is intended or given. Insulcon does not accept any liability for any loss, injury, or damage resulting from the use of this product.